# HP 27fw 27-inch Display





## **Product overview**

- Appealing, ultra-thin design: Built from lightweight, high-strength metal with a matte finish and high-polished resin, this ultra-slim display brings home a modern look and feel without the premium price tag.
- **Stunning from edge-to-edge:** With its vivid IPS panel, this micro-edge display delivers ultra-wide viewing angles and crisp, clear picture quality. It's an expansive viewing experience, perfect for dual display setups.
- **Packed with entertainment features:** Experience the sharp, clear difference FHD resolution brings to all your content. And thanks to AMD FreeSync<sup>™</sup>, PC gaming is free of blur and lag.<sup>(1)(2)</sup>

### **Key specifications**

- Viewable image area: 27-inch display, diagonally measured
- Aspect ratio: 16:9
- Contrast: Dynamic Ratio 10M:1<sup>(3)</sup>
- Resolution: 1920 x 1080 @ 60 Hz (Full HD)<sup>(2)</sup>
- Connectivity:

1 x VGA 2 x HDMI

Exterior color: White

## **Product features**

- **Full HD display / 1080p display:** Be prepared for brilliant visuals and crisp images with the unforgettable quality of this stunning FHD display.<sup>(1)</sup>
- Micro-edge display: With virtually no bezel encircling the display, an ultra-wide viewing experience provides for seamless multi-monitor set-ups.
- Step up to the best: No matter where you stand, an HP IPS monitor delivers clear, vivid images. IPS technology ensures image accuracy and consistency across the ultra-wide viewing spectrum.
- **Virtually edge-to-edge panel:** Expansive is the only way to describe the maximized screen area you get with the beautiful edge-to-edge glass panel.



# Impossibly thin. Irresistibly priced.

Get the crisp, clear picture quality you crave with this ultra-slim, micro-edge display. From browsing content to streaming entertainment—it allows you to see your world in a whole new way.

## **Additional product features**

- AMD FreeSync<sup>™</sup> technology: See and feel the difference of fluid, responsive gameplay. By synchronizing the refresh rate with your GPU, AMD<sup>®</sup> FreeSync<sup>™</sup> makes display stutter, input lag, and screen tears ancient history.<sup>style=\*>(2)</sup>
- **Anti-glare panel:** Enjoy the sun and your favorite content with this anti-glare panel. Non-reflective and low gloss, means you'll get less glare while you're outside.
- Share the panoramic view: Ultra-wide 178° angle viewing with consistent detail and vibrant color.
- Dual HDMI: Dual HDMI ports means more options and more devices you can connect for big screen, FHD visuals.<sup>(2)</sup>
- **Compact, sleek design:** Get everything you need in one elegant package. Just one connection to the wall eliminates cable clutter. Slim design gives you more room for an enhanced computing experience.
- Modern design: With a sleek design this contemporary display perfectly compliments your latest device and seamlessly integrates within the modern home.
- **Adjust your view:** Adjust the screen to your personal preference with a 5° forward or 25° backward tilt.
- Seamless visuals: Videos and games come to life with less stutter or blur for more realistic play with smooth 5 milisecond gray-to-gray response time.
- Low Blue Light: Using the Low Blue Light mode subtly shifts your display's colors to a warmer spectrum, while making whites more natural and putting less strain on your eyes.

## **Environmentally conscious**

• Energy efficient design and components help reduce power consumption and energy costs.

## **Warranty and support**

• Rest easy and work confidently with an HP standard 1 year limited warranty. Certain restrictions and exclusions apply.<sup>(8)</sup>



#### **Monitor specifications**

Panel type <ul><li>IPS // LED backlight</li><li>27-inch display, diagonally measured</li><li>Vertical: 178°</li><li>Vertical: 178°</li><li>Starte treatment</li><li>Anti-Gare panel</li><li>Recommendon</li><li>120-1080@60 Hz (Full HD)<sup>12</sup></li><li>Appect ratio</li><li>120-1080@60 Hz (Full HD)<sup>12</sup></li><li>120-1080@60 Hz (Full HZ)<sup>12</sup></li>&lt;</ul>	Joitwale	lets you partition your screen so that multiple application windows can be open at the same time, and even saves user-preferred settings for any easy startup.
Viewable image area> 27-inch display, diagonally measuredViewing angle> Horizontal: 178° • Vertical: 178°Surface treatment> Anti-Glare panelResolution (recommended)> 1920 x 1080 @ 60 Hz (Full HD) <sup>62</sup> (Full HD)Aspect ratio> 16:9Contrast ratio> Static Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>63</sup> Brightness (typical)> 300 nits <sup>64</sup> Color gamut> 72%Color support• Up to 16.7M colors with the use of FRC technologyPixel pitch• 0.3114 (H) mm x 0.3114 (V) mm • 82 PPIPanel active area> 597.89 mm x 336.31 mmScan range• Morizontal: • VORA 301 68 KHz 	Software	User control OSD settings: HP My Display Smart software also
Viewable image area> 27-inch display, diagonally measuredViewing angle> Horizontal: 178° • Vertical: 178°Surface treatment> Anti-Glare panelResolution (recommended)> 1920 × 1080 @ 60 Hz (Full HD) <sup>(2)</sup> (recommended)Aspect ratio> 16:9Contrast ratio> Static Ratic: 1000:1 • Dynamic Ratic: 10M:1 <sup>(2)</sup> Brightness (typical)> 300 nits <sup>(4)</sup> Color gamut> 72%Color support• Up to 16.7M colors with the use of FRC technologyPixel pitch• 0.3114 (H) mm × 0.3114 (V) mm • 82 PPIPanel active area> 597.89 mm × 336.31 mmScan range* Horizontal: • VGA 30 to 80 KHz • HDMI 30 to 86 KHz • Vertical: VGA 30 to 80 KHz • HDMI 48 to 75 HzResponse time> 5ms GtG w/DD • 14ms GtG (typ) • 28 ms GtG (max)Connectivity• VGA • 2 × HDMI • HDCP SupportPower supply• ExternalMaximum power consumption• 27WConsumption• 0.3WEnergy saving/standby mode• 9.35 in x 8.05 inDetachable stand Guersions• Yes SupportDetachable stand Guersions• 24.08 in (W) x 8.04 in (D) x 17.68 in (H) dimensions	•	
Viewable image area> 27-inch display, diagonally measuredViewing angle> Horizontai: 178°Surface treatment> Anti-Glare panelResolution (recommended)> 1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio> 16:9Contrast ratio> Static Ratio: 1000:1 Dynamic Ratio: 1001:1 <sup>(2)</sup> Brightness (typical)> 300 nits <sup>60</sup> Color gamut> 72%Color support> Up to 16.7M colors with the use of FRC technologyPixel pitch> 0.3114 (H) mm x 0.3114 (V) mm · 82 PPIPanel active area> 597.89 mm x 336.31 mmScan range> Korizontai: VGA 30 to 80 KHz HDMI 30 to 86 KHz · Vertical: VGA 50 to 60Hz HDMI 48 to 75 HzResponse time> Sms GtG w/OD · 14ms GtG (typ) · 28 ms GtG (max)Power supplyExternalMaximum power consuption> 27WConnectivity· 0.3WPixel atom by · VGA · 2 x HDMI · HDCP SupportPower supplyExternalMaximum power consuption· -5 to +25 degreesBase area footprint• 9.35 in x 8.05 inDetachable stand· Yes, ships detachedSecurity lock ready· YesUnpackaged dimensions> 24.08 in (W) x 8.04 in (D) x 17.68 in (H)		
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1 Dynamic Ratio: 100:1 <sup>(4)</sup> Color gamut       72%         Color support       Up to 16.7M colors with the use of FRC technology         Pixel pitch       0.3114 (H) mm x 0.3114 (V) mm 82 PPI         Panel active area       597.89 mm x 336.31 mm         Scan range       Horizontal: VGA 30 to 80 KHz HDMI 30 to 86 KHz         Vertical:       VGA 50 to 60Hz HDMI 30 to 86 KHz         Vertical:       VGA 50 to 60Hz HDMI 30 to 86 KHz         Vertical:       VGA 50 to 60Hz HDMI 30 to 86 KHz         Vertical:       VGA 50 to 60Hz HDMI 30 to 86 KHz         Vertical:       VGA 50 to 60Hz HDMI 30 to 80 KHz         Vertical:       VGA 50 to 60Hz HDMI 30 to 80 KHz         Vertical:       VGA 50 to 60Hz         Response time       5 Sms GtG (max)         Connectivity       VGA 2 X HDMI HDCP Support         Power supply       External         Maximum power consumption       27W         Energy saving/standby mode       9		0.11 //
Viewable image area27-inch display, diagonally measuredViewing angle: Horizontal: 178° · Vertical: 178°Surface treatment: Anti-Glare panelResolution (recommended): 1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio: 16:9Contrast ratio: Static Ratio: 1000:1 · Dynamic Ratio: 10011 · Dynamic Ratio: 10011 		• 24.08 in (W) x 8.04 in (D) x 17.68 in (H)
Viewable image area27-inch display, diagonally measuredViewing angle: Horizontal: 178° · Vertical: 178°Surface treatment: Anti-Glare panelResolution (recommended): 1920 × 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio: 16:9Contrast ratio: Static Ratio: 1000:1 · Dynamic Ratio: 10011 · Dynamic Ratio: 10010 · 14ms GtG (typ) · 28 ms GtG (max)Connectivity· VGA	Security lock ready	• Yes
Viewable image area27-inch display, diagonally measuredViewing angle: Horizontal: 178° · Vertical: 178°Surface treatment: Anti-Glare panelResolution (recommended): 1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio: 16:9Contrast ratio: Static Ratio: 1000:1 · Dynamic Ratio: 10M:1 <sup>(2)</sup> Brightness (typical): 300 nits <sup>(4)</sup> Color gamut: 72%Color support: Up to 16.7M colors with the use of FRC technologyPixel pitch: 0.3114 (H) mm x 0.3114 (V) mm · 82 PP1Panel active area: 597.89 mm x 336.31 mmScan range: Horizontal: VGA 30 to 80 KHz · Vertical: · VGA 50 to 60Hz · HDMI 48 to 75 HzResponse time: Sms GtG W/DD · 14ms GtG (tpp) · 28 ms GtG (max)Connectivity: VGA · 2x HDMI · HDCP SupportPower supply: ExternalMaximum power consumption: 27WEnergy saving/standby mode: 0.31W		Yes, ships detached
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 100:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)       300 nits <sup>(4)</sup> Color gamut       72%         Color support       Up to 16.7M colors with the use of FRC technology         Pixel pitch       0.3114 (H) mm x 0.3114 (V) mm · 82 PPI         Panel active area       597.89 mm x 336.31 mm         Scan range       Horizontal: VGA 30 to 80 KHz HDMI 30 to 86 KHz         V Vertical: VGA 50 to 60Hz HDMI 48 to 75 Hz         Response time       5 sms GtG (w/OD · 14ms GtG (typ) · 28 ms GtG (max)         Connectivity       VGA · 2 x HDMI · HDCP Support         Power supply       External         Maximum power consumption       27W         Energy saving/standby mode       0.3W	Base area footprint	• 9.35 in x 8.05 in
Viewable image area• 27-inch display, diagonally measuredViewing angle• Horizontal: 178° • Vertical: 178°Surface treatment• Anti-Glare panelResolution (recommended)• 1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio• 16:9Contrast ratio• Static Ratio: 1000:1 • Dynamic Ratio: 1001:1 • Dynamic Ratio: 1001:1 	Tilt	• -5 to +25 degrees
Viewable image area27-inch display, diagonally measuredViewing angleHorizontal: 178° Vertical: 178°Surface treatmentAnti-Glare panelResolution (recommended)1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio16:9Contrast ratioStatic Ratio: 1000:1 Dynamic Ratio: 10011 Dynamic Ratio: 10012 Dynamic Ratio: 10012 Dynamic Ratio: 10012 Dynamic	saving/standby	• 0.3W
Viewable image area27-inch display, diagonally measuredViewing angleHorizontal: 178° Vertical: 178°Surface treatmentAnti-Glare panelResolution (recommended)1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> (Fecommended)Aspect ratio16:9Contrast ratioStatic Ratio: 1000:1 Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)300 nits <sup>(4)</sup> Color gamut72%Color supportUp to 16.7M colors with the use of FRC technologyPixel pitch0.3114 (H) mm x 0.3114 (V) mm 82 PPIPanel active area597.89 mm x 336.31 mmScan rangeHorizontal: VGA 30 to 80 KHz HDMI 30 to 86 KHz Vertical: VGA 50 to 60Hz HDMI 48 to 75 HzResponse timeSms GtG w/OD 14ms GtG (typ) 28 ms GtG (max)ConnectivityVGA 2 x HDMI HDCP Support	-	• 27W
Viewable image area27-inch display, diagonally measuredViewing angleHorizontal: 178° Vertical: 178°Surface treatmentAnti-Glare panelResolution (recommended)1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> (Factomended)Aspect ratio16:9Contrast ratioStatic Ratio: 1000:1 Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)300 nits <sup>(4)</sup> Color gamut72%Color supportUp to 16.7M colors with the use of FRC technologyPixel pitch0.3114 (H) mm x 0.3114 (V) mm 82 PPIPanel active area597.89 mm x 336.31 mmScan rangeHorizontal: VGA 30 to 80 KHz HDMI 30 to 86 KHzVertical: VGA 50 to 60Hz HDMI 48 to 75 HzSms GtG (typ) 28 ms GtG (max)ConnectivityVGA 2 x HDMI	Power supply	• External
Viewable image area27-inch display, diagonally measuredViewing angleHorizontal: 178° • Vertical: 178° • Vertical: 178°Surface treatmentAnti-Glare panelResolution (recommended)1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio16:9Contrast ratioStatic Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)300 nits <sup>(4)</sup> Color gamut72%Color supportUp to 16.7M colors with the use of FRC technologyPixel pitch0.3114 (H) mm x 0.3114 (V) mm • 82 PPIPanel active area597.89 mm x 336.31 mmScan rangeHorizontal: VGA 30 to 80 KHz HDMI 30 to 86 KHz · Vertical: VGA 50 to 60Hz HDMI 48 to 75 HzResponse time5ms GtG w/OD • 14ms GtG (typ)	Connectivity	• 2 x HDMI
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)       300 nits <sup>(4)</sup> Color gamut       72%         Color support       Up to 16.7M colors with the use of FRC technology         Pixel pitch       0.3114 (H) mm x 0.3114 (V) mm · 82 PPI         Panel active area       597.89 mm x 336.31 mm         Scan range       Horizontal: · VGA 30 to 80 KHz · HDMI 30 to 86 KHz · Vertical: · VGA 50 to 60Hz	Response time	• 14ms GtG (typ)
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)       300 nits <sup>(4)</sup> Color gamut       72%         Color support       Up to 16.7M colors with the use of FRC technology         Pixel pitch       0.3114 (H) mm x 0.3114 (V) mm • 82 PPI         Panel active area       597.89 mm x 336.31 mm	Juin range	VGA 30 to 80 KHz HDMI 30 to 86 KHz • Vertical: VGA 50 to 60Hz
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)       300 nits <sup>(4)</sup> Color gamut       72%         Color support       Up to 16.7M colors with the use of FRC technology         Pixel pitch       0.3114 (H) mm x 0.3114 (V) mm • 82 PPI		
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)       300 nits <sup>(4)</sup> Color gamut       72%         Color support       Up to 16.7M colors with the use of FRC technology         Pixel pitch       0.3114 (H) mm x 0.3114 (V) mm	Danal active area	
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)       300 nits <sup>(4)</sup> Color gamut       72%	Pixel pitch	• 0.3114 (H) mm x 0.3114 (V) mm
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup> Brightness (typical)       300 nits <sup>(4)</sup>		• Up to 16.7M colors with the use of FRC technology
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1 • Dynamic Ratio: 10M:1 <sup>(3)</sup>		
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup> Aspect ratio       16:9         Contrast ratio       Static Ratio: 1000:1	Brightness (typical)	•
Viewable image area       27-inch display, diagonally measured         Viewing angle       Horizontal: 178°         Vertical: 178°       Vertical: 178°         Surface treatment       Anti-Glare panel         Resolution (recommended)       1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup>	Contrast ratio	Static Ratio: 1000:1
Viewable image area       • 27-inch display, diagonally measured         Viewing angle       • Horizontal: 178°         • Vertical: 178°       • Vertical: 178°         Surface treatment       • Anti-Glare panel         Resolution       • 1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup>		• 16:9
Viewable image area       • 27-inch display, diagonally measured         Viewing angle       • Horizontal: 178°         • Vertical: 178°		• 1920 x 1080 @ 60 Hz (Full HD) <sup>(2)</sup>
Viewable image area       • 27-inch display, diagonally measured         Viewing angle       • Horizontal: 178°	Surface treatment	Anti-Glare panel
	Viewing angle	
Panel type     • IPS w/ LED backlight	Viewable image area	27-inch display, diagonally measured
	Panel type	• IPS w/ LED backlight

On screen display	<ul> <li>Brightness, Contrast, Color Control, Input Control, Image Control, Power Control, Menu Control, Management, Language, Information, Exit</li> <li>User Programmable Modes: 20</li> <li>Monitor Control Buttons: Menu/ok, Information/"-", Input/"+", Auto/QV/Exit, Power button</li> </ul>
Languages	<ul> <li>English, French, German, Italian, Dutch, Spanish, Japanese, Portuguese, Traditional Chinese, and Simplified Chinese</li> </ul>
Certifications	<ul> <li>Windows 10, 8, 7 Microsoft WHQL Certification</li> <li>(0EM) CB, CE, TUV-BAUART/ISO9241, CSA/CSA-NRTL, FCC, ICES, VCCI, CCC, China CEL, BSMI, KCC /KC/E-standby, ES7.0, EUP Lot 6 and Lot 26, GEMS, MEPS</li> <li>HDMI certification</li> </ul>

#### **Environmental features**

LED backlights	Mercury-free LED backlighting
Backlight lamp life	• 30K hours
Arsenic-free	Arsenic-free display glass <sup>(6)</sup>
Low halogen	Low-voltage halogen design <sup>(5)</sup>
Certifications	<ul> <li>EPEAT<sup>®</sup> Silver registered<sup>(7)</sup></li> <li>Energy Star<sup>®</sup> qualified</li> </ul>

#### **Accessories & warranty**

What's in the box	<ul> <li>A/C power cable 1.9 m (6.2 ft)</li> <li>Power adapter 1.0 m (3.3 ft)</li> <li>HDMI cable 1.8 m (5.9 ft)</li> <li>Quick set up poster</li> <li>Service phone list card</li> </ul>
Limited warranty	- Protected by a one-year HP limited warranty. Certain restrictions and exclusions apply. $^{\scriptscriptstyle (B)}$

#### **Additional information**

Product number	• 3KS64AA#ABA
Ad embargo date	• 04/03/2018
UPC Code	• 192018806108
Country of origin	• China
Tariff number	• 8528520000
Pallet information	<ul> <li>Dimensions: 47.87 in (L) × 37.80 in (W) × 4.96 in (H)</li> <li>Total weight: 793.66 lb (GQ) / 778.23 lb (HQ)</li> <li>Layers: 4 (GQ) / 5 (HQ)</li> <li>Products per layer: 12</li> <li>Total products per pallet: 48 (GQ) / 60 (HQ)</li> </ul>

#### Learn more at hp.com



